

JISAN HEAVY INDUSTRY LTD.
Professional Excavator Attachment Manufacturer



Address: NO 41, Jinfeng Road, Fushan District, Yantai, China. 265500

Tel: +86 18615951533 Fax: +86-5353468305

E-mail: scottning@jisanbr.com Website: www.jisanbr.net

Facebook: www.facebook.com/jisanheavyindustry



LONG REACH

The long reaches are used for dredging rivers, port construction, railway construction and groundwork construction, with high extensive operation scope, high efficiency and high security.

DLK SERIES LONG REACHES FEATURE

- ◆ Original excavator performance
- ◆ Made of high strength steel plate
- ◆ Improve operation scope
- ◆ Operation scope 13-32M
- ◆ Completely match with the hydraulic crusher, hydraulic breaker, vibro ripper etc.
- ◆ Designed with spray pipe to reduce dust
- ◆ Convenient for installation and detachment
- ◆ We can design and customize according to your requirement



Item	Model	Unit	DLKE1200	DLKE2000-1	DLKE2000-2	DLKE3000	DLKE3500-1	DLKE3500-2
Total length		mm	13000	15380	18000	18000	20000	22000
Weight		kg	3000	4000	4200	5200	6000	6500
Max dig depth		mm	9000	11340	12200	12200	14500	16100
Maximum extensive scope		mm	12500	15100	17600	17600	19600	21600
Max dig height		mm	11300	12510	13500	13720	14920	16100
Folding height		mm		2980	3040	3210	3210	3400
Bucket volume		m ³	0.3	0.6	0.4	0.4	0.5	0.6
Suitable excavator		Ton	12	20	20	30	35	35

PILE HAMMER

- ◆ DLK series vibrating pile hammer is specially designed for excavator usage.
- ◆ Easily operating and make full use of the hydraulic power of excavator; the hydraulic pressure is adjusted according to the different working situation to reach a proper impact force. This new generation product increases the production efficiency and realizes versatility of excavator.
- ◆ Applied to pull or pile sheet piles, I-steel piles, cement square pile, cylinder pile and many other shapes



Item	Model	Unit	DLKP08	DLKP10	DLKP14	DLKP20
Weight		kg	1450	1550	1650	1800
Eccentric Moment		Nm	40	50	65	85
Frequency		rpm	2800	2800	2800	2800
Pressure		bar	280	280	300	300
Flow		lpm	155	168	210	255
Clamp Weight		kg	C12-300 CHB-360 C30-350			
Arm Weight		kg	A150-450 A200-550 A250-600 A300-750 A350-900			
Application Excavator		Ton	20-24	24-32	30-40	40-45